

Servant, Dunbrack, McKenzie & MacDonald Ltd. **NOVA SCOTIA LAND SURVEYORS & CONSULTING ENGINEERS**

36 Oland Crescent

Bayers Lake Business Park Halifax, Nova Scotia B3S 1C6

Fax Web

Phone (902) 455-1537 (902) 455-8479 sdmm.ca

RAYMOND A. LANDRY MASC., P.Eng., LEED Green Associate

CHRISTOPHER J. FORAN

DANIEL S. GERARD

H. JAMES McINTOSH

P.Eng., NSLS, CLS

KEVIN A. ROBB

BLAKE H. TRASK

ADAM J. PATTERSON

P.Eng., NSLS

P.Eng., NSL5

P.Eng., NSLS

NSLS

P.Eng

GEOFFREY K. MacLEAN P.Eng.

RACHAEL W. KYTE P.Eng., LEED Green Associate ALEXANDER W. PULSIFER

P.Eng.

MICHAEL S. TANNER

December 16, 2019

Halifax Water 450 Cowie Hill Road Halifax, NS

From: Ray Landry, P.Eng.

File No. <u>1-4-</u>160 (34817)

Hanwell Building, Block CL, Hanwell Drive, Middle Sackville, NS -

Sanitary Lateral Size Confirmation

Project Summary:

	Residential (Multi-Unit)		
Building	51 Units		
Values from client			

References:

1. Halifax Water (HW) Design & Construction Specifications, 2018 Edition, Section 4.2.2:

• $Q = [1.25 \times (a \times M)] + b$

Where;

Q = Sanitary sewer flow.

1.25 = Safety factor.

a = Average dry weather flow.

M = Peaking factor using Harmon Formula; M = 1 + [14 / (4 + P^{0.5})]

b = Long-term infiltration/inflow allowance.

P = Population in thousands

• Residential Average Dry Weather Flow:

300 L/day per person

• Multi-Unit Dwelling Population:

2.25 people per unit

• Infiltration allowance:

0.28 L/hagross/s



Calculation Summary:

Population Estimate (P)

Reference:

P: HW Section 4.2.1 Residential (Multi-Unit):

2.25 people per unit

P = 2.25 people per unit x 51 Units

= 115 people

P = 115 people (or 0.115)

Dry Weather Flow (a)

Reference:

a: HW Section 4.2.2: Residential: 300 L/day per person

a = 300 L/day per person x 115 people

= 34,500 L/day (or 0.40 L/s)

Infiltration (b)

Reference:

HW Section 4.2.2: Infiltration allowance: 0.28 L/hagross/s

Lot Area = $5,380 \text{ m}^2 = 0.54 \text{ ha}$

b: 0.28 L/hagross/s x 0.54 ha

= 0.15 L/s

Peaking Factor (M)

 $M = 1 + [14 / (4 + P^{0.5})]$

 $M = 1 + [14 / (4 + (0.115)^{0.5})]$

= 4.22

Sanitary Sewer Flow (Q)

 $Q = [1.25 \times (a \times M)] + b$

 $Q = [1.25 \times (0.40 \text{ L/s} \times 4.22)] + 0.15 \text{ L/s}$ = 2.26 L/s

Sanitary Lateral Size Confirmation:

A 200 mm diameter PVC lateral at 2.0 % slope has a capacity of 67 L/s. With Q = 2.26 L/s, the proposed lateral will have sufficient flow capacity. For additional information or discussion regarding these findings please contact the undersigned.

Regards,

Servant, Dunbrack, McKenzie & MacDonald Ltd.

Ray Landry, P.Eng.

Project Engineer

Z \SDMM\34000-34999\34800\34817\Design\sanitary\34817 \Sonitary Flow Confirmation.docx

2|Page

LEGEND				
EXISTING		PROPOSED		
⊗/⊗BF	CURB STOP/GATE/BUTTERFLY VALVE	⊗/⊗BF		
•	FIRE HYDRANT	•		
∹∢	SIAMESE SPRINKLER CONNECTION	∹<		
12 / 2 / 0	CATCH BASIN/PIT	11/12/0		
♦/♦ *	POWER POLE/LIGHT POLE	Φ/Φ - #		
€	TREE	€}		
T	STREET SIGN	•		
— CAS —— CAS —	GAS LINE	— cus —— cus —		
	WATER MAIN/SERVICE	—— w ——⊗—		
SAN	SANITARY MANHOLE & PIPE	SAN		
STM	STORM MANHOLE & PIPE	STM		
SAN/STM —	COMBINED SEWER	—— SAN/STM ———		
	PROPERTY LINE/BOUNDARY			
	BUILDING			

NOTES

- EXISTING WATER, STORM & SANITARY SEWER, AND GAS UNDERGROUND PIPING BASED ON HW & HERITAGE GAS GIS DATA AND RECORDS. CONTRACTOR TO VERIFY EXACT LOCATIONS AND ELEVATIONS IN THE FIELD.
- 2. PROPERTY BOUNDARIES HAVE BEEN COMPILED FROM VARIOUS SOURCES AND ARE SUBJECT TO SURVEY.
- 3. ALL WORK SHALL BE COMPLETED IN ACCORDANCE WITH NOVA SCOTIA REGULATIONS AND HRM BY-LAWS, HALIFAX WATER DESIGN AND CONSTRUCTION SPECIFICATIONS (LATEST EDITION) AND HRM MUNICIPAL SERVICE SYSTEM GUIDELINES "RED BOOK" (LATEST EDITION).
- 4. CONTRACTOR TO HAVE SERVICES LOCATED IN THE FIELD PRIOR TO DIGGING
- CONTRACTOR TO REMOVE EXISTING LATERALS TO THE MAIN AND REMOVE OLD VALVES.





36 OLAND CRESCENT
BAYERS LAKE BUSINESS PARK
HALIFAX, NOVA SCOTIA
OFFICE: (902) 455-1537
FAX: (902) 455-8479

HANWELL BUILDING SERVICING SCHEMATIC HANWELL DRIVE, MIDDLE SACKVILLE Project No.: 1- 13- 49 (348 Scale: 1:8

Date:

1:500 16 Dec 2019 WM FARES

C1

